



July 4, 2018  
 \_\_\_\_\_  
 Date

## Supply and Delivery of Various IT Equipment for the Single Carpeta Roll-Out

BJMP ITB Reference No.: G-2018-008

### SUPPLEMENTAL/BID BULLETIN NO. 1

Please be advised of the following Clarifications/Amendments to the Bidding Documents:

### VII. Technical Specifications

FROM		TO
<b>3. Biometric Scanner for Visitor Management and Inmates Kiosk</b>		
3.1 Brand	SECUGEN Hamster Plus*	SECUGEN Hamster Plus or Hamster Pro 20 <i>(compatible with the Single Carpeta System)</i>
3.3 Image Size	260 x 300 pixels	260 x 300 pixels or 300 x 400 pixels
3.4 Platen Size	16.1 mm x 18.2 mm	14.6 mm x 17.9 mm mm or 18.2 mm x 22.9 mm
3.5 Effective Sensing Area	13.2 mm X 15.2 mm	13.2 mm X 15.2 mm or 15.2 mm x 20.3 mm
3.10 Supply Voltage / Max Current	5 Vdc, 140 Ma	5 Vdc, 140 mA or 150mA
3.11 Dimension	27 X 40 X 73 mm (without stand); 53 x 73 x 84 mm (with stand)	27 X 40 X 73 mm (without stand); 53 x 73 x 84 mm (with stand) or 53.9 x 58.5 x 31.6 mm
3.12 Weight	100 g (without stand); 165 g (with stand)	100 g (without stand); 165 g (with stand) or 98g
3.14 Operating Temperature	20 °C to 65 °C @ 90% RH or Less, Non Condensing	20 °C to 65 °C
3.15 Standards Supported	ANSI INCITS 378, BioAPI, ISO/IEC 19794-2, ISO/IEC 19794 – 4, FCC, CE, RoHS	(ANSI INCITS 378, BioAPI, ISO/IEC 19794-2, ISO/IEC 19794 – 4) or (FIPS 201, FBI PIV & Mobile ID FAP 20, INCITS 378, ISO/IEC 19794-2, 19794-4)
3.16 Operating System	Supports Windows 7, Windows Server 2008 R2, Android, Java, Linux	Supports Windows 10, 8.1, 8, 7 Android, Java, Linux
3.17 Software	Scan Demo, Enrollment Kit, WSQ, NFIQ	Bundled SDK
<b>1. Biometric Scanner for Inmate's Booking</b>		
4.1 Brand	FUTRONIC FS641D Flat Fingerprint Scanner*	FUTRONIC FS641D Flat Fingerprint Scanner <i>(Compatible with the single Carpeta System)</i>
<b>5. Signature Tablet</b>		
5.1 Brand	*TOPAZ SigLite LCD 1x5, Interactive LCD, with backlit	TOPAZ SigLite LCD 1x5, Interactive LCD, with backlit <i>(Compatible with the Single Carpeta System)</i>

5.6 Signing Area	4.4" X 1.3" (12 mm X 33 mm)	4.4" X 1.3" (112 mm X 33 mm)
<b>6. Digital Web Camera</b>		
6.1 Technology	Fluid Crystal Technology	<i>Remove</i>
<b>8. Network Server</b>		
8.1 Power Supply	At least 1 x 550W High Efficiency Power Supply	At least 1 x 460W Power Supply
<b>9. Application Server</b>		
9.35	<b>COMPLIANCE</b>	
	If the machine will be re-allocated to other regional office, the manufacturer of the brand being offered must have the capacity to provide nationwide onsite support and provide the manufacturer's central support hotline and email	<i>Remove</i>
9.36		Implementation and installation in BJMP-NHQ Data Center Cabinet
<b>12. Firewall</b>		
<b>12.1 Hardware Specifications</b>		<b>12.1 Hardware Specifications</b>
12.1.3 Memory : Min 8 GB		12.1.3 Memory : Minimum 12 GB
12.1.4 HDD Storage : Min 120 GB SSD		12.1.4 HDD Storage : Minimum 180 GB SSD
<b>12.2 Security Performance</b>		<b>12.2 Security Performance</b>
12.2.1 Firewall Throughput : 18Gbps		12.2.1 Firewall Throughput : Minimum 30 Gbps
12.2.2 IPS throughput : Minimum 4.2 Gbps		12.2.2 IPS throughput : Minimum 8.5 Gbps
12.2.3 VPN throughput : Minimum 1.5 Gbps		12.2.3 VPN throughput : Minimum 3.2 Gbps
12.2.4 Antivirus throughput (proxy) : Minimum 2.8 Gbps		12.2.4 Antivirus throughput (proxy) : Minimum 6 Gbps
		12.24 Product Certifications (Safety, EMC) : CB, CE, FCC Class A, CTick
		12.25 Implementation and installation in BJMP-NHQ Data Center Cabinet
33. Trainers and Installers must be a Certified Technical Engineer(s) or Technical Representative of the Manufacturer of the product offered by the Bidder		33. Trainers and Installers must be a Certified Technical Engineer(s) or Technical Representative of the Manufacturer of the product offered by the Bidder for Network Server, Application Server, Access Point, Firewall

  
**RUEL S RIVERA**  
 Jail Chief Superintendent  
 BAC Chairperson  
 BJMP -NHQ